

DESCRIPTION

Green Splicing Tape. Polyester Film Silicone Tape. 72yd Green Splicing. Custom slit to width

APPLICATION PROCESS

Suitable for powder coating masking tape. Applications up to 437_F. High tack adhesive system offer masking protection. Removal from substrates without adhesive transfer or residue. Tear and break resistance. Resistance to corrosive chemicals

MATERIAL DESCRIPTION

SIZE (width x length)	72 yd
COLOR	Emerald
ADHESIVE TYPE	Pressure-Sensitive Tape
CONSTRUCTION	Single Coated
SELF WOUND	Yes
RELEASE LINER MATERIAL	N/A
RELEASE LINER THICKNESS	
WEIGHT	

TECHNICAL DATA

ADHESIVE LAYER	Silicone
BACKING/CARRIER MATERIAL	PET Film
BACKING/ADHESIVE THICKNESS	2 mil PET Film
TOTAL THICKNESS	3.56 mil
ADHESION TO STEEL	40 oz/in
TENSILE STRENGTH	22 kg/25 mm
ELONGATION	100% at break
TEMPERATURE APPLICATION	N/A
TEMPERATURE OPERATING	437°F

Physical and performance characteristics shown are obtained from tests recommended by vendor. Quality Assurance and Technical Service Departments do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

Surfaces to be bonded to should be dry, clean and free from oil and grease.

Typical shelf life is one (1) year from date of manufacture (DOM). Recommended storage conditions: 40-60% Humidity, 60°F to 80°F

Note: The information listed above has been obtained from controlled laboratory tests and is reliable, but should not be used for the purpose of writing specifications. It is offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. It is recommended that the prospective user determine the product suitability before adapting for commercial use.



195 Polk Avenue • Nashville, Tennessee 37210
 p: 615.255.1775 • f: 615.256.6557 • 800.643.5996
can-dotape.com