

Protective Paper. Protective paper with high tack adhesive. It is wrinkle free and leaves no residue or oil. Custom slit to width

APPLICATION PROCESS

Recommended for use on small to medium computer cut graphics and die-cut lettering and is especially good for use with small and medium size plotters. Release coated for an easy unwind, provides excellent adhesion for transfer and installation and offers a simple release after use. Used for the clean pick-up and transfer of vinyl lettering and graphics.

MATERIAL DESCRIPTION	
SIZE (width x length)	100 yd
COLOR	White
ADHESIVE TYPE	Pressure-Sensitive Tape
CONSTRUCTION	Single Coated
SELF WOUND	Yes
RELEASE LINER MATERIAL	N/A
RELEASE LINER THICKNESS	
WEIGHT	

TECHNICAL DATA	
ADHESIVE LAYER	Rubber
BACKING/CARRIER MATERIAL	Paper
BACKING/ADHESIVE THICKNESS	
TOTAL THICKNESS	4.0 to 4.5 PSTC-33
ADHESION TO STEEL	15.0 oz/in PSTC I
TENSILE STRENGTH	
ELONGATION	3-4% at break PSTC-31
TEMPERATURE APPLICATION	N/A
TEMPERATURE OPERATING	N/A

Physical and perfomance characteristics shown are obtained from tests recommended by vendor. Quality Assurance and Technical Service Departments do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

Surfaces to be bonded to should be dry, clean and free from oil and grease.

Typical shelf life is one (1) year from date of manufacture (DOM). Recommended storage conditions: 40-60% Humidity, 60°F to 80°F

Note: The information listed above has been obtained from controlled laboratory tests and is reliable, but should not be used for the purpose of writing specifications. It is offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. It is recommended that the prospective user determine the product suitability before adapting for commercial use.



