

DESCRIPTION

Premium PTFE Coated Fiberglass. PTFE-Coated Fiberglass provides high PTFE content for long release life in many demanding applications. Custom slit to width

APPLICATION PROCESS

Used as conveyor belts, release sheets, gaskets, in heat and sealing and packaging applications. Suitable for direct food contact under 21CFR177.1551

MATERIAL DESCRIPTION	
SIZE (width x length)	36 yd
COLOR	Natural
ADHESIVE TYPE	Pressure-Sensitive Tape
CONSTRUCTION	Single Coated
SELF WOUND	Yes
RELEASE LINER MATERIAL	N/A
RELEASE LINER THICKNESS	
WEIGHT	9.40 oz/yd
Resin Content	68%

TECHNICAL DATA	
ADHESIVE LAYER	N/A
BACKING/CARRIER MATERIAL	Cloth
BACKING/ADHESIVE THICKNESS	
TOTAL THICKNESS	6 mil
ADHESION TO STEEL	Check Specs
TENSILE STRENGTH	Check Specs
ELONGATION	Check Specs
TEMPERATURE APPLICATION	
TEMPERATURE OPERATING	-240°F to 500°F

Physical and performance characteristics shown are obtained from tests recommended by vendor. Quality Assurance and Technical Service Departments do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

Note: The information listed above has been obtained from controlled laboratory tests and is reliable, but should not be used for the purpose of writing specifications. It is offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. It is recommended that the prospective user determine the product suitability before adapting for commercial use.



195 Polk Avenue • Nashville, Tennessee 37210
 p: 615.255.1775 • f: 615.256.6557 • 800.643.5996
can-dotape.com