

DESCRIPTION

Aluminum Foil Tape with liner. Specially formulated antimicrobial, extreme weather, acrylic adhesive. Dead soft aluminum foil with excellent adhesion and quick stick application at a temperature as low as 0°F. Custom slit to width

APPLICATION PROCESS

Specially designed for taping joints and seams against moisture and vapor foil jacketing facing and FSK blankets. Conformability to curved surfaces, strong bond to a variety of substrates, made in the USA,. Approved for use by the US Coast Guard in accordance with International Maritime Org. (IMO) A.653(16) and ISO 65659.

MATERIAL DESCRIPTION	
SIZE (width x length)	50 yd
COLOR	Silver
ADHESIVE TYPE	Pressure-Sensitive Tape
CONSTRUCTION	Single Coated
SELF WOUND	Yes
RELEASE LINER MATERIAL	Densified Kraft Paper
RELEASE LINER THICKNESS	3.6 mil
WEIGHT	60#

TECHNICAL DATA	
ADHESIVE LAYER	Acrylic
BACKING/CARRIER MATERIAL	Aluminum Foil
BACKING/ADHESIVE THICKNESS	1.7 mil
TOTAL THICKNESS	2.0 mil
ADHESION TO STEEL	64 oz/in PSTC-103 ASTM D-3330
TENSILE STRENGTH	N/A
ELONGATION	N/A
TEMPERATURE APPLICATION	N/A
TEMPERATURE OPERATING	N/A

Physical and performance characteristics shown are obtained from tests recommended by vendor. Quality Assurance and Technical Service Departments do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

Surfaces to be bonded to should be dry, clean and free from oil and grease.

Typical shelf life is one (1) year from date of manufacture (DOM). Recommended storage conditions: 40-60% Humidity, 60°F to 80°F

Note: The information listed above has been obtained from controlled laboratory tests and is reliable, but should not be used for the purpose of writing specifications. It is offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. It is recommended that the prospective user determine the product suitability before adapting for commercial use.



195 Polk Avenue • Nashville, Tennessee 37210
 p: 615.255.1775 • f: 615.256.6557 • 800.643.5996
can-dotape.com