

DESCRIPTION

Black Premium Gaffer's Tape. Heavy-duty vinyl coated cloth tape with a natural rubber based adhesive and matte-finish. Moisture-resistant backing with excellent flexibility. High tack tape with excellent adhesion for superior performance. Non-reflective backing for low gloss. Retains flexibility and conformability in both low and high temperature applications. Custom slit to width.

APPLICATION PROCESS

Protect and anchor wiring in the photography, music and film industries. General patch and repair, bookbinding, vinyl seat repair, color coding and temporary carpet edge hold-down. Wrapping or bundling wire, metals and plastics where residue-free removal is desired. Matte-finish for less reflectivity and low sheen. Excellent durability and conformability. High tack for a variety of surfaces. Clean removal – no residue. Can contribute towards satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED. Low VOC content

MATERIAL DESCRIPTION

SIZE (width x length)	60 yd
COLOR	Black
ADHESIVE TYPE	Pressure-Sensitive Tape
CONSTRUCTION	Single Coated
SELF WOUND	Yes
RELEASE LINER MATERIAL	N/A
RELEASE LINER THICKNESS	
WEIGHT	

TECHNICAL DATA

ADHESIVE LAYER	Rubber
BACKING/CARRIER MATERIAL	Matte-Finish Vinyl Coated Cloth
BACKING/ADHESIVE THICKNESS	N/A
TOTAL THICKNESS	11.5 mil ASTMD-100
ADHESION TO STEEL	50 oz/in PSTC-101
TENSILE STRENGTH	42 lb/in ASTM D-1000
ELONGATION	N/A
TEMPERATURE APPLICATION	N/A
TEMPERATURE OPERATING	40° to 200°F

Physical and performance characteristics shown are obtained from tests recommended by vendor. Quality Assurance and Technical Service Departments do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

Surfaces to be bonded to should be dry, clean and free from oil and grease.

Typical shelf life is one (1) year from date of manufacture (DOM). Recommended storage conditions: 40-60% Humidity, 60°F to 80°F

Note: The information listed above has been obtained from controlled laboratory tests and is reliable, but should not be used for the purpose of writing specifications. It is offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. It is recommended that the prospective user determine the product suitability before adapting for commercial use.



195 Polk Avenue • Nashville, Tennessee 37210
p: 615.255.1775 • f: 615.256.6557 • 800.643.5996
can-dotape.com