

DESCRIPTION

Kraft Paper Tape. General purpose tape for a variety of substrates. Very high adhesion and Kraft flatback paper with synthetic rubber-based adhesive. ASTM D 6123/D 6123M-97 (2012), Type II Strong, flexible and conformable backing. High cross-directional tensile strength. Aggressive, high tack adhesive with excellent holding power. Tape color blends well with kraft cartons. Resists curling, abrasion and water

APPLICATION PROCESS

Designed for hand and machine carton sealing and splicing applications. Offers strength, extensibility, conformability, and high cross direction tensile for general purpose applications. Splicing of various substrates. General purpose packing, binding, holding, tabbing, reinforcing, banding and patching tape for variety of substrates

MATERIAL DESCRIPTION	
SIZE (width x length)	2" x 60 yd
COLOR	Brown Kraft
ADHESIVE TYPE	Pressure-Sensitive Tape
CONSTRUCTION	Single Coated
SELF WOUND	Yes
RELEASE LINER MATERIAL	N/A
RELEASE LINER THICKNESS	
WEIGHT	

TECHNICAL DATA	
ADHESIVE LAYER	Rubber
BACKING/CARRIER MATERIAL	Kraft Flatback Paper
BACKING/ADHESIVE THICKNESS	
TOTAL THICKNESS	6.2 mil ASTM D-3652
ADHESION TO STEEL	85 oz/in ASTM D-3330
TENSILE STRENGTH	35 lb/in width ASTM D-3759
ELONGATION	6%
TEMPERATURE APPLICATION	60°F to 150°F
TEMPERATURE OPERATING	

Physical and performance characteristics shown are obtained from tests recommended by vendor. Quality Assurance and Technical Service Departments do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

Surfaces to be bonded to should be dry, clean and free from oil and grease.

Typical shelf life is one (1) year from date of manufacture (DOM). Recommended storage conditions: 40-60% Humidity, 60°F to 80°F

Note: The information listed above has been obtained from controlled laboratory tests and is reliable, but should not be used for the purpose of writing specifications. It is offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. It is recommended that the prospective user determine the product suitability before adapting for commercial use.



195 Polk Avenue • Nashville, Tennessee 37210
 p: 615.255.1775 • f: 615.256.6557 • 800.643.5996
can-dotape.com