

DESCRIPTION

Aluminum Alloy Foil Tape with a pressure sensitive adhesive and paper liner. The aggressive rubber adhesive sticks will to most surfaces and the paper liner makes for convenient and reliable use.

APPLICATION PROCESS

Ideal for sealing aluminum faced insulation seams and joints General repair and maintenance. Temporary and emergency repair of metal surfaces. UL 723 rated for flame and smoke characteristics. Can be used under all weather conditions. Matches aluminum foil-faced duct systems and insulation. Resists water vapor, odor and smoke transmission. Acts as vapor barrier to insure the integrity of the insulation system

MATERIAL DESCRIPTION

SIZE (width x length)	2" x 50 yd
COLOR	Silver
ADHESIVE TYPE	Pressure-Sensitive Tape
CONSTRUCTION	Single Coated
SELF WOUND	Yes
RELEASE LINER MATERIAL	Paper
RELEASE LINER THICKNESS	
WEIGHT	

TECHNICAL DATA

ADHESIVE LAYER	Rubber
BACKING/CARRIER MATERIAL	Aluminum Foil
BACKING/ADHESIVE THICKNESS	2 mil
TOTAL THICKNESS	3.6 mil (0.09 mm) ASTM D-3652
ADHESION TO STEEL	90 oz/in ASTM D-3330
TENSILE STRENGTH	17 lb/in width ASTM D-3759
ELONGATION	3% at break
TEMPERATURE APPLICATION	10°F to 180°F
TEMPERATURE OPERATING	-10°F to 180°F

Physical and performance characteristics shown are obtained from tests recommended by vendor. Quality Assurance and Technical Service Departments do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

Surfaces to be bonded to should be dry, clean and free from oil and grease.

Typical shelf life is one (1) year from date of manufacture (DOM). Recommended storage conditions: 40-60% Humidity, 60°F to 80°F

Note: The information listed above has been obtained from controlled laboratory tests and is reliable, but should not be used for the purpose of writing specifications. It is offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. It is recommended that the prospective user determine the product suitability before adapting for commercial use.



195 Polk Avenue • Nashville, Tennessee 37210
 p: 615.255.1775 • f: 615.256.6557 • 800.643.5996
can-dotape.com