

**357B-2**  
**PREMIUM GRADE DUCT TAPE**

**CAN-DO NATIONAL TAPE**  
**TECHNICAL DATA SHEET**

**DESCRIPTION**

Multi-purpose duct tape

**PRODUCT APPLICATION**

Waterproof repairs  
Heavy Duty packaging and bundling  
Seaming and securing underlayment materials  
Media Blasting  
Seaming and Sealing for heavy PE sheeting and tarps

**FEATURES & BENEFITS**

Abrasion and Puncture resistant  
Crisp, straight tear  
Moisture, solvent, chemical resistant  
Aggressive adhesion to smooth and rough surfaces  
Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED

**NOTES**

- Surfaces to be bonded to should be dry, clean and free from oil and grease.
- Recommended storage conditions: 40-60% Humidity, 60°F to 80°F
- The information listed above has been obtained from controlled laboratory tests and is reliable, but should not be used for the purpose of writing specifications. It is offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. It is recommended that the prospective user determine the product suitability before adapting for commercial use.

**NOMINAL VALUES**

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

**BACKING** PE Coated Cloth

**COLOR** Black

**ADHESIVE** Rubber

**ADHESION TO STEEL (oz/in)** 95  
PSTC-101

**TENSILE STRENGTH (lbs/in of width)** 50  
ASTM D-1000

**ELONGATION (% at break)** 13%

**TOTAL THICKNESS (mils)** 13  
ASTM D-1000

**TEMPERATURE OPERATING** 40°F to 200°F



195 Polk Avenue  
Nashville, TN 37210  
P: 615.255.1775  
F: 615.256.6557  
[www.can-dotape.com](http://www.can-dotape.com)